

Quadtone RIP UV Transmission Density Test
Epson 2400

	5%	10%	15%	20%	25%	30%	35%	40%	45%	50%	55%	60%	65%	70%	75%	80%	85%	90%	95%	100%
K (black)	0.25	0.37	0.5	0.63	0.75	0.87	0.98	1.1	1.21	1.31	1.41	1.52	1.61	1.7	1.79	1.88	1.97	2.04	2.13	2.17
C (cyan)	0.22	0.3	0.38	0.44	0.5	0.55	0.61	0.66	0.71	0.75	0.79	0.83	0.87	0.9	0.94	0.97	1	1.02	1.05	1.06
M (magenta)	0.17	0.19	0.22	0.25	0.27	0.3	0.32	0.35	0.37	0.39	0.41	0.43	0.45	0.47	0.49	0.51	0.53	0.55	0.56	0.57
Y (yellow)	0.29	0.43	0.59	0.74	0.89	1.035	1.2	1.34	1.48	1.59	1.71	1.82	1.93	2.02	2.11	2.21	2.3	2.37	2.44	2.47
LC (light cyan)	0.17	0.2	0.22	0.24	0.25	0.27	0.3	0.32	0.34	0.35	0.37	0.39	0.4	0.42	0.44	0.45	0.47	0.48	0.49	0.5
LM (light magenta)	0.14	0.15	0.16	0.17	0.175	0.18	0.19	0.2	0.21	0.22	0.23	0.235	0.24	0.26	0.27	0.28	0.28	0.285	0.29	0.295
LK (light black)	0.21	0.27	0.34	0.4	0.46	0.52	0.59	0.64	0.7	0.75	0.8	0.86	0.91	0.95	1	1.05	1.09	1.13	1.17	1.19
LLK (light-light black)	0.16	0.18	0.21	0.23	0.25	0.26	0.29	0.31	0.32	0.34	0.35	0.37	0.39	0.41	0.42	0.44	0.45	0.47	0.48	0.485

